



SAE 0W16 API SP

Technical Data Sheet



PACKAGING:

1L, 4L, 5L, 7L, 20L, 25L, 60L, 208L

DESCRIPTION:

Volkio 0W-16 is a high-performance, low-viscosity engine oil designed for modern vehicles, providing excellent fuel efficiency and engine protection. The "0W" indicates superior cold-start protection, allowing the oil to flow quickly even in extremely low temperatures. The "16" ensures optimal lubrication at high operating temperatures. Volkio 0W16 is formulated to help to increase engine efficiency and improve fuel economy benefits, while providing outstanding overall engine protection.

BENEFITS:

- Protects and cleans exhaust catalysts and DPFs.
- Excellent engine protection.
- Helps fuel efficiency.
- Suitable for extended drain intervals.
- Reduces chlorine content to meet the environmental requirements.
- Low Oil Top up.
- Better cold starting.

SPECIFICATIONS:

Rulexx Plus 0W16 SP full synthetic motor oil meets and exceeds the requirements of all major car manufacturers and the following standards:

ILSAC GF-6; ACEA A5/B5; Chrysler 6395; GM 6094M, 4718M; Ford WSS M2C946-A, M2C929-A; Honda HTO-06

BMW: long life listing, Mercedes Benz – sheet 229.10.

TYPICAL PROPERTIES:

TEST	FREQUENCY	RESULT
Appearance	VISUAL	Bright & Clear
Color	ASTM D 1500	Neutral
Kin. Viscosity @100°C	ASTM D 445	6.0–8.2 Cst
Kin. Viscosity @40°C	ASTM D 445	41.2
Viscosity Index	ASTM D 2270	170
Density @ 60/60F	ASTM D 1298	0.839
Pour Point	ASTM D 97	≤ -51°C
Flash Point	ASTM D 92	≥230°C
Water Content	ASTM D 6034	-ve
Antifoam	ASTM D 892	Pass

APPLICATION:

This product meets or exceeds the requirements of the latest API and ILSAC industry specifications for petrol and hybrid engine oils, as well as the requirements of many major American engine manufacturers. Suitable for use in passenger cars.