



## SAE 5W30 API SN

Semi Synthetic

Technical Data Sheet



### PACKAGING:

1L, 4L, 5L, 7L, 20L, 25L, 60L, 208L

### DESCRIPTION:

Volkio 5W-30 is an enhanced, premium-quality, synthetic technology engine oil that meets the latest engine oil specifications in the industry. It is designed to provide an excellent level of protection and performance under the most demanding conditions. It is a high reach quality lubricant, completely manufactured, uniquely figured out to meet the most recent execution prerequisites of present day motors.

### BENEFITS:

- Its special and exclusive formula helps your vehicle maintain maximum horsepower by reducing sludge formation.
- Its additive package provides excellent protection against engine wear and deposit formation.
- Provides superior engine protection during start-up.
- Excellent protection at high temperatures thanks to its formulation with a high-quality base oil.

### SPECIFICATIONS:

Volkio 5W30 SN full synthetic motor oil meets and exceeds the requirements of all major car manufacturers and the following standards:

ILSAC GF-5; ACEA A5/B5; Chrysler 6395; GM 6094M, 4718M;

Ford WSS M2C946-A, M2C929-A; Honda HTO-06, BMW: long life listing, Mercedes Benz – sheet 229.10.

### TYPICAL PROPERTIES:

TEST	FREQUENCY	RESULT
Appearance	VISUAL	Bright & Clear
Color	ASTM D 1500	Neutral
Kin. Viscosity @100°C	ASTM D 445	9.3-12.5 Cst
Kin. Viscosity @40°C	ASTM D 445	REPORT
Viscosity Index	ASTM D 2270	140
Density @ 60/60F	ASTM D 1298	0.850
Pour Point	ASTM D 97	≤ -39°C
Flash Point	ASTM D 92	≥ 225°C
Water Content	ASTM D 6034	-ue
Antifoam	ASTM D 892	Pass

### APPLICATION:

5W30 SN semi-synthetic recommend it in particular for the following vehicle types and conditions:

The latest gasoline engine technologies, Passenger vehicles, SUVs, light trucks and vans, Turbochargers and High-performance engines.