



SAE 10W30 API SN MOTO

Technical Data Sheet

PACKAGING:

800ML



DESCRIPTION:

Volkio fully synthetic Moto Oil 10W-30 SN Lubricant reinforced with Extreme Pressure additives to guarantee protection and life time of the gears. High lubricant properties to reduce wear and increase engine durability. High detergent and dispersant properties to maintain engine cleanliness. JASO MA2 lubricant to ensure highest friction possible between friction plates of wet clutch and guarantee perfect clutch lock up at start-up, acceleration and full speed. Easy gear shifting.

BENEFITS:

- Special cleaning agents and dispersants help prevent deposit formation.
- Thermal and oxidation stability.
- Maintains power and economy by minimizing wear.
- Helps keep engines clean for smoother operation
- Engine Cleanliness and low combustion residue.

SPECIFICATIONS:

Volkio 10W40 SN oil meets and exceeds the requirements of all major car manufacturers and the following standards:

API SN,SM,SL

JASO MA,JASO MA2

JASO 4T Clutch performance

TYPICAL PROPERTIES:

TEST	FREQUENCY	RESULT
Appearance	VISUAL	Bright & Clear
Color	ASTM D 1500	Neutral
Kin. Viscosity @100°C	ASTM D 445	11Cst
Kin. Viscosity @40°C	ASTM D 445	71.2
Viscosity Index	ASTM D 2270	143
Density @ 60/60F	ASTM D 1298	0.874
Pour Point	ASTM D 97	≤-36°C
Flash Point	ASTM D 92	≥220°C
Water Content	ASTM D 6034	-ve
Antifoam	ASTM D 892	Pass

APPLICATION:

Street & road bikes, trails, off-road bikes... fitted with 4 Stroke engines, integrated gearbox or not, wet or dry clutch, engines with or without catalytic converters. Suitable for all engines requiring SAE 10W-30 viscosity grade fuel economy oil. Other uses: ATVs, mopeds.