



SAE 0W40 API SP

Technical Data Sheet



PACKAGING:

1L, 4L, 5L, 7L, 20L, 25L, 60L, 208L

DESCRIPTION:

Volkio 0W-40 advanced full synthetic motor oil is engineered to deliver excellent all-around performance in gasoline and diesel engines (without Diesel Particulate Filters or DPFs) with the latest technological advancements. 0W-40 motor oil provides exceptional cleaning power and wear protection to keep your engine running like new in most driving conditions, from mild to extreme.

BENEFITS:

- Protects and cleans exhaust catalysts and DPFs.
- Excellent engine protection.
- Helps fuel efficiency.
- Suitable for extended drain intervals.
- Reduces chlorine content to meet the environmental requirements.
- Low Oil Top up.
- Better cold starting.

SPECIFICATIONS:

Volkio 0W40 SP fully synthetic motor oil meets and exceeds the requirements of all major car manufacturers and the following standards:

ACEA ACEA A3/B3, A3/B4 API SP, MB 229.31/51/52, OV 0401547, BMW LL-04, Rn17 / RN0700/710; Chrysler 6395; GM 6094M, 4718M; Ford WSS M2C946-A, M2C929-A; Honda HTO-06

TYPICAL PROPERTIES:

TEST	FREQUENCY	RESULT
Appearance	VISUAL	Bright & Clear
Color	ASTM D 1500	Neutral
Kin. Viscosity @100°C	ASTM D 445	15.1 Cst
Kin. Viscosity @40°C	ASTM D 445	86.2
Viscosity Index	ASTM D 2270	185
Density @ 60/60F	ASTM D 1298	0.845
Pour Point	ASTM D 97	≤-48°C
Flash Point	ASTM D 92	≥225°C
Water Content	ASTM D 6034	-ve
Antifoam	ASTM D 892	Pass

APPLICATION:

Turbo chargers, Direct injection, Diesel engines (without DPFs), Hybrids