



## SAE 15W40 API CJ-4

Technical Data Sheet



### PACKAGING:

1L, 4L, 5L, 7L, 20L, 25L, 60L, 208L

### DESCRIPTION:

Volkio SAE 15W40 API CJ-4 is premium diesel engine oil surpasses the most demanding European specifications and meets market requirements for fuel-efficient performance. Formulated with carefully selected premium base fluids and advanced additives, it delivers exceptional protection and efficiency for modern diesel engines.

### BENEFITS:

- Excellent engine protection by providing outstanding protection against corrosive & abrasive wear.
- Protects against start-up wear in cold conditions through excellent low-temperature fluidity.
- Maintains power and economy by minimizing wear.
- Improved shear stability maintains viscosity in-grade under severe, high-temperature service conditions.
- Excellent low-temperature pumpability ensures smooth cold starting and improved fuel economy.
- Engine Cleanliness and low combustion residue.

### SPECIFICATIONS:

Rulexx Plus 15W40 CJ-4 Diesel Engine oil meets and exceeds the requirements of International Standards:  
API CJ-4/CK-4/SN, ACEA E9-16  
MB 228.31, MTU Type 2.1, CAT ECF-3, Deutz DQC III-10 LA (obsolete), III-18 LA, Ford WSS-M2C171-F1, CES 20081  
Volvo VDS 4, Mack EO-O PP, Renault RLD-3, DDC93K218, MAN M3575 (obsolete)

### TYPICAL PROPERTIES:

TEST	FREQUENCY	RESULT
Appearance	VISUAL	Bright & Clear
Color	ASTM D 1500	Neutral
Kin. Viscosity @100°C	ASTM D 445	15 Cst
Kin. Viscosity @40°C	ASTM D 445	115.6
Viscosity Index	ASTM D 2270	135
Density @ 60/60F	ASTM D 1298	0.875
Pour Point	ASTM D 97	≤ -27°C
Flash Point	ASTM D 92	≥ 230°C
Water Content	ASTM D 6034	-ve
Antifoam	ASTM D 892	Pass

### APPLICATION:

15W40 CJ-4 Diesel Engine Oil can be used in the latest highly rated turbo charged 4 stroke diesel engines under all operating conditions.