



SAE 5W40 API SN

Technical Data Sheet



PACKAGING:

1L, 4L, 5L, 7L, 20L, 25L, 60L, 208L

DESCRIPTION:

Volkio 5W-40 SN is a premium, fully synthetic engine oil designed for modern gasoline engines, offering excellent fuel efficiency and engine protection. It is a high reach quality lubricant, completely manufactured, uniquely figured out to meet the most recent execution prerequisites of present day motors.

BENEFITS:

- Its special and exclusive formula helps your vehicle maintain maximum horsepower by reducing sludge formation.
- Excellent performance for the higher power and speeds in modern engines.
- Enhances life of crankcase
- The outstanding thermal stability and resistance to oxidation of this oil prevent any degradation, even in extreme usage conditions which helps to extend engine life.
- Custom designed which helps to meet manufacturer's requirement to extend interval between oil changes.

SPECIFICATIONS:

Volkio 5W40 SN full synthetic motor oil meets and exceeds the requirements of all major car manufacturers and the following standards:

ILSAC GF-5/API SN, GM 6094M, Ford WSS-M2C-945A/946A/947A, Chrysler MS 6395, GM Dexos1™

TYPICAL PROPERTIES:

TEST	FREQUENCY	RESULT
Appearance	VISUAL	Bright & Clear
Color	ASTM D 1500	Neutral
Kin. Viscosity @100°C	ASTM D 445	14 Cst
Kin. Viscosity @40°C	ASTM D 445	92.85 Cst
Viscosity Index	ASTM D 2270	155
Density @ 60/60F	ASTM D 1298	0.850
Pour Point	ASTM D 97	≤-39°C
Flash Point	ASTM D 92	≥220°C
Water Content	ASTM D 6034	-ve
Antifoam	ASTM D 892	Pass

APPLICATION:

SN motor oil can be used in all naturally aspirated, injected, turbo-charged and multivalve passenger car engines.