



## ATF DEXRON VI

Technical Data Sheet



### PACKAGING:

1L, 4L, 60L, 208L

### DESCRIPTION:

Volkio Dexron VI ATF DEX-VI is a fully synthetic high-performance fluid meeting the most demanding requirements of GENERAL MOTORS 6speed automatic transmission system. Exceeds the service fill of 2006 and new GM vehicles, where a DEXRON-VI fluid is recommended. ATF DEX-VI provides effective wear protection and optimal friction characteristics for smooth gear shifts. Highly stable to mechanical wear at various working temperature, consistent fluid characteristics and excellent shear stability to provide robust protection of transmission systems. Engineered for longer drain intervals versus the older DEXRON fluids.

### BENEFITS:

- Low viscosity formulation provides fuel economy benefits compared with fluids formulated to meet Dexron® IIIH or earlier specifications.
- Premium synthetic formulation gives Outstanding oxidative resistance extending transmission life.
- Enhanced friction durability improves shifting performance.

### SPECIFICATIONS:

Volkio Dexron VI meets or exceeds following International and Builder specifications

GM DEXRON®-VI

- FORD MERCON®
- CHRYSLER ATF+4
- FORD WSS-M2C922-A1
- FORD WSS-M2C938-A

### TYPICAL PROPERTIES:

TEST	FREQUENCY	RESULT
Appearance	VISUAL	Bright & Clear
Color	ASTM D 1500	Red
Kin. Viscosity @100°C	ASTM D 445	5.58
Kin. Viscosity @40°C	ASTM D 445	26.7
Viscosity Index	ASTM D 2270	154
Density @ 60/60F	ASTM D 1298	0.850
Pour Point	ASTM D 97	≤ -44°C
Flash Point	ASTM D 92	≥ 186
Water Content	ASTM D 6034	-ve
Antifoam	ASTM D 892	Pass

### APPLICATION:

Recommended for use in modern automatic transmissions and steering gears of passenger cars, vans and light commercial trucks where DEXRON-VI fluid is required. Backward compatible to older GM vehicles whenever DEXRON is specified.