



OIL- SMOKE, LEAK-STOP

Technical Data Sheet

PACKAGING:

300ml Bottle



DESCRIPTION:

VOLKIO Oil Stop Leak is a specialty product meant for use when common problems like oil leaks or exhaust smoke occurs. It is specially designed to help rejuvenate seals and gaskets and improve sealing at valve guides, piston rings and cylinder walls. This results in a reduction or stop of oil loss and oil contamination and in better compression and thus superior engine performance.

There are several ways engine lubricant leak into combustion chambers.

1-Through valves then leak into intake and exhaust manifolds. Then leak into combustion chamber.

2-Through gaps between piston rings and cylinder into combustion chambers. When Engine Burn Lubricant in combustion chamber engine will emit white smoke.

BENEFITS:

- Stops and prevents oil leakages through seals
- Eliminates the need for expensive engine repair
- Makes seals swell back to original size and regain all-new pliability
- Prolongs the service life of the engine
- Reduces emission of hazardous exhaust gases
- Improves engine performance by enhancing motor compression

Usage Guide:

Add one bottle of Volkio Stop Oil & Smoke into engine oil compartment. It will take about a few hours to a few days to repair the engine smoke and oil leak problem.

Once the engine smoke and oil leak problem resolved. Replace the engine oil to new engine oil within one month. Sufficient to treat 6-4 liters engine oil.

TYPICAL PROPERTIES:

TEST	ASTM	RESULT
API Gravity	D4052	21.1
Specific Gravity @ 60°F	D4250	0.9273
Density @ 60°F Lbs/Gal	D4052	7.693
Viscosity @40°C, cSt	D445	44.5
Flash Point COC°F	D92	435
Color		Amber

APPLICATION:

Run engine to normal operating temperature and switch off. Add contents of bottle to engine oil and run for 5 minutes to ensure thorough mixing.