



ATF DEXRON III

Technical Data Sheet



PACKAGING:

1L, 4L, 60L, 208L

DESCRIPTION:

Volkio Dexron III ATF is approved for use in all General Motors automatic transmissions. It is licensed against Dexron® VI which supersedes all previous Dexron® specifications for General Motors Holden applications. Volkio Dex III ATF is formulated from high tech basestocks combined with advanced additive technology. Volkio Dex III ATF is designed to provide better heat resistance, cold flow capabilities and transmission shudder resistance than conventional automatic transmission fluids.

BENEFITS:

- Low viscosity formulation provides fuel economy benefits compared with fluids formulated to meet Dexron® IIIH or earlier specifications.
- Premium synthetic formulation gives Outstanding oxidative resistance extending transmission life.
- Enhanced friction durability improves shifting performance.

SPECIFICATIONS:

Volkio Dexron III meets or exceeds following International and Builder specifications
Allison C-4 Fluids, Allison TES, 389, Caterpillar TO-2 Fluids Chrysler transmissions prior to Chrysler MS-9602 or MS-7176, Ford MERCON®, Ford M2C138-CJ, M2C 166-H Fluids, GM DEXRON® III-H, III-G, III-F, III-E, III-D MAN 339 Z1 and V1, Z2 and V2, MB 236.1, 236.5, 236.6, 236.7, 236.9, 6336

TYPICAL PROPERTIES:

TEST	FREQUENCY	RESULT
Appearance	VISUAL	Bright & Clear
Color	ASTM D 1500	Red
Kin. Viscosity @100°C	ASTM D 445	7-9
Kin. Viscosity @40°C	ASTM D 445	30.2
Viscosity Index	ASTM D 2270	185
Density @ 60/60F	ASTM D 1298	0.850
Pour Point	ASTM D 97	≤ -49°C
Flash Point	ASTM D 92	≥ 220
Water Content	ASTM D 6034	-ve
Antifoam	ASTM D 892	Pass

APPLICATION:

ATF is particularly suitable for use in automatic transmissions of car & light trucks and On-highway & Off-highway heavy-duty automatic transmissions. It is also recommended for power steering, torque converters and hydraulic systems, where such types of fluids are specified.