



SP MATIC ATF LV

Technical Data Sheet



PACKAGING:

1L, 4L, 60L, 208L

DESCRIPTION:

Volkio SP Matic is a synthetic, multi-functional ATF fluid with fuel-saving properties. This product has been specially developed for modern, automatic transmissions by various car manufacturers that require a high-grade, low-viscosity ATF with fuel-saving properties. Developed to help leaks, maximize transmission performance, reduce transmission wear and maintain smooth shifting longer than conventional fluids. Volkio Multi ATF LV is suitable for use in broad range of ATF applications including most Ford, GM, Toyota & Honda models as well as Dex/Merc, Mercon LV and many more applications. Volkio Multi ATF LV is recommended for use in most belt and chain-driven continuously variable transmissions.

BENEFITS:

- Excellent oxidation resistance enabling extended drain intervals.
- Compatible with rubbers, elastomers, and metal components for improved sealing and wear protection.
- Outstanding shear stability ensures long-lasting viscosity retention.
- Superior low-temperature fluidity for smooth cold starts.
- Excellent compatibility with transmission components.

SPECIFICATIONS:

Volkio SP MATIC ATF LV meets or exceeds following International and Builder specifications

Aisin Warner JWS 3324 / AW-1

Ford Mercon LV, Mercon SP; GM Dexron VI

Honda ATF DW-1; Hyundai / Kia SP-IV, SP-IV M, SP-IV RR, SPH-IV

Mazda FZ; Mercedes MB 236.41; Nissan Matic K, Matic S, Matic W

Toyota / Lexus ATF WS; Tesla ATF9/EDF2

VW G 053 001 / G 053 025 / G 055 005 / G 055 025;

VW G 055 162 / G 055 540 / G 060 162

TYPICAL PROPERTIES:

TEST	FREQUENCY	RESULT
Appearance	VISUAL	Bright & Clear
Color	ASTM D 1500	Red
Kin. Viscosity @100°C	ASTM D 445	5.90
Kin. Viscosity @40°C	ASTM D 445	29
Viscosity Index	ASTM D 2270	175
Density @ 60/60F	ASTM D 1298	0.846
Pour Point	ASTM D 97	≤ -48°C
Flash Point	ASTM D 92	≥ 212
Water Content	ASTM D 6034	-ve
Antifoam	ASTM D 892	Pass

APPLICATION:

SP Matic ATF LV is a synthetic, multi-functional ATF fluid with fuel-saving properties. This product has been specially developed for modern, automatic transmissions by various car manufacturers that require a high-grade, low-viscosity ATF with fuel-saving properties. Consult the advice database for tailor-made product advice.