



SP MATIC ATF

Technical Data Sheet



PACKAGING:

1L, 4L, 60L, 208L

DESCRIPTION:

Volkio SP Matic is a synthetic, multi-functional ATF fluid with fuel-saving properties. This product has been specially developed for modern, automatic transmissions by various car manufacturers that require a high-grade, low-viscosity ATF with fuel-saving properties. Developed to help leaks, maximize transmission performance, reduce transmission wear and maintain smooth shifting longer than conventional fluids. Volkio Multi ATF LV is suitable for use in broad range of ATF applications including most Ford, GM, Toyota & Honda models as well as Dex/Merc, Mercon LV and many more applications. Volkio Multi ATF LV is recommended for use in most belt and chain-driven continuously variable transmissions.

SPECIFICATIONS:

Volkio SP MATIC ATF meets or exceeds following International and Builder specifications

Aisin Warner JWS 3309 / JWS 3317; Allison C4/TES-389/TES-295

BMW ATF 6 (83 22 2 355 599); BMW 7045E/8072B/LA2634/LT71141

Chrysler / Dodge / Jeep MS 9602, ATF +4, ATF +3; Fiat 9.55550-AV4

Ford Mercon V, WSS-M2C922-A1, WSS-M2C924-A

GM Dexron IID, Dexron IIE, Dexron IIIG, Dexron IIHH

Honda ATF-Z1 (CVT istisna olmaqla); Hyundai/Kia SP-II/SP-III/RED-1K, Isuzu ATF II/III

Jaguar JLM 20238/20292/21044; JASO M315 Tip 1A

Mazda M-III/Tip T-IV, JWS 3309. Mercedes MB 236.14, MB 236.12, Mercedes MB 236.91, MB 236.11, MB 236.10; Mitsubishi SP-II, SP-III, ATF-J2, Nissan Matic-D, Matic-J, Matic-K

Subaru ATF HP, Suzuki ATF 3314/3317, Toyota / Lexus T, T-II, T-III, T-IV

Volvo 1161540; VW G 052 025 / G 052 055, VW G 052 162 / G 052 990 / G 055 025

ZF TE ML 11A, 11B, ZF ATF 1375.4 (6HP Transmissiyalar) G 055 025;

VW G 055 162 / G 055 540 / G 060 162

TYPICAL PROPERTIES:

TEST	FREQUENCY	RESULT
Appearance	VISUAL	Bright & Clear
Color	ASTM D 1500	Red
Kin. Viscosity @100°C	ASTM D 445	5.90
Kin. Viscosity @40°C	ASTM D 445	29
Viscosity Index	ASTM D 2270	149
Density @ 60/60F	ASTM D 1298	0.846
Pour Point	ASTM D 97	≤ -48°C
Flash Point	ASTM D 92	≥ 212
Water Content	ASTM D 6034	-ve
Antifoam	ASTM D 892	Pass

APPLICATION:

Volkio Multi-Vehicle ATF meets the needs of a broad range of transmission designs and power steering applications. Volkio Multi-Vehicle ATF is not recommended for use in CVT or DCT transmissions.